OPTICAL TELECOMMUNICATION OUTLET

2LINE OTO

The OTO is a fiber optic outlet that allows easy termina- tion of cables in an office and home environment. In a compact small housing all features are provided for an advanced FTTH installation.

- **flat and modern design can be surface-mounted on standard electrical outlet**
- **guided and sealed cable entrance from the bottom or the back with integrated or additional strain relief**

FACTS

Advantages:

- capacity up to 4 fibers by providing 2 connection points for SC and LC duplex adapters and 4 splices
- all internal fibers are protected, guided and minimum bend radius controlled; over length can be stored
- removable splicing holder supports mechanical crimp splice protector and heat shrink splice protector
- molded solid plastic box made of ABS
- color RAL 9010
- environmental protection class IP20, -10° C to +60° C
- fire protection class UL94 V-0
- guiding and storage for 4 fiber pigtails, 140 cm
- 2 adapter places for SC and LCdx
- input cable diameter 3 - 7 mm through boot

Scope of delivery:

- preassembled with adapter and pigtails, splicing protection for crimp splice or shrink splice; strain relief and cable management

Dimensions:

- 80 mm x 120 mm x 25 mm (W x H x D)

Properties:

- capacity: 2 adapters, 4 pigtails/splices

ZweiCom-Hauff GmbH
Geiselroter Heidle 1
73494 Rosenberg, Germany

Tel.: +49 7967 9008-30
Fax: +49 7967 9008-99

office@zweicom-hauff.com